

EXCA100IP4



4 Megapixel - HD^{plus} IR Indoor/Outdoor IP Dome Camera

Low Profile, High Resolution

2-Way
Audio

4MP
HD^{plus}

True
Day/Night

WDR
Wide
Dynamic
Range

3DNR
Noise
Reduction

ONVIF
Latest
Version

SD DVR

4 Megapixel Imaging Sensor, Day/Night, Superflux Smart IR LED, 3.6 mm Lens, Multiple Streaming, Edge Recording with Micro SD Card Slot, Corridor Mode, D-WDR, 3DNR, PoE, Audio, BNC Video Service Output, Latest ONVIF, H.264/H.265/MJPEG Compression, IP65 Rated.

FEATURES

- ✓ 4 Megapixel Imaging Sensor - ultra high definition resolution
- ✓ Wide Angle 3.6mm lens
- ✓ Up to 4MP @ 20fps, up to 3MP @ 30fps, up to 2MP @ 30fps
- ✓ Superflux Smart IR LED with 10 meter IR range
- ✓ Edge recording with Micro SD card slot for local video archiving (Max 128GB)
- ✓ H.264, H.265 & MJPEG video compression
- ✓ Triple Streaming & RTSP, up to 12000kb per second bit rate
- ✓ Wide Dynamic Range (> 120dB) & 2D/3D Noise Reduction
- ✓ Supports 2-Way Audio
- ✓ IP65 Ingress Protection Rated
- ✓ Latest ONVIF Compliant

SPECIFICATIONS

Resolution	4 MP Imaging Sensor (2592 x 1520) Ultra High Definition
Video Compression	H.264 / H.265 / MJPEG
Resolution / fps	4MP @ 20fps / 3MP @ 30fps / 2MP @ 30fps
Bit Rate (CBR / VBR)	Main Stream:500KB-12000KB / Sub Stream:100KB-6000KB
Minimum Illumination	0 lux IR On 0.05 lux Color
Lens	3.6mm
Field of View (FOV)	75°
IR LED / Range	1 Superflux IR LED / 10 meters
Corridor Mode	YES, 9:16 Aspect Ratio for Narrow Aisle View
Video Service Output	BNC
ONVIF Compliance	Latest ONVIF
Edge Recording	Micro SD Card Slot, Max 128GB (SD Card Not Included)
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Power	PoE / 12 VDC / 2.5W (IR LED OFF) / 5W (IR LED ON)
Dimensions / Weight	100mm (W) x 53mm (H) / 400g (0.88 lbs.)
Ingress Protection	IP65

ACCESSORIES



AM33
Wedge Mount



POE800-70W
8CH POE Switch



AM44
Wall Mount



POE1600-130W
16CH POE Switch



AM43
Pendant Mount



EXNVR
Professional NVR