## EXCA233IP4

Motorized

Zoom

Autofocus

**3DNR** 

Noise

Reduction



## 4 Megapixel - HD *plus* Indoor Recessed Mount Dome IP Camera with Motorized Zoom & Autofocus

Exclusive Dual Mount Feature - Surface or Recessed Installation

4 Megapixel Imaging Sensor, Indoor Dual Mount Surface/Recessed Dome IP Camera with Motorized 2.8-12mm Optical Zoom Lens with Autofocus. Also features H.264/H.265 & MJPEG Multi Streaming, Edge Recording with Micro SD Card Slot, Corridor Mode, WDR, 3DNR, ICR Cut Filter, PoE, Audio In/Out, Alarm In/Out, BNC Video Service Output, Latest ONVIF.

## **FEATURES**

Surface Mount

**WDR** 

Wide

Dynami Range

2-Way

Audio

Alarm

((丸)) ((丸))

**I/O** 

4MP

**HD**<sup>plus</sup>

<del>.</del>0:

Day/Night

4 Megapixel Imaging Sensor - ultra high definition resolution  $\mathbf{\mathbf{V}}$ 

**Recessed Mount** 

**ONVIF** SD DVR

- 3-Axis Gimbal with 2.8 12mm motorized optical zoom lens featuring automatic focus  $\mathbf{\mathbf{N}}$
- ✓ Up to 4MP @ 20fps, up to 3MP @ 30fps, up to 2MP @ 30fps

Latest Version

- Latest ONVIF  $\mathbf{\mathbf{I}}$
- Dual Mount Feature Recessed mount for low profile & minimal footprint, plus standard surface mount  $\mathbf{\mathbf{N}}$
- Edge recording with Micro SD card slot for local video archiving (Max 128GB)  $\mathbf{I}$
- Latest High Efficiency H.265 video compression plus H.264 & MJPEG  $\mathbf{\mathbf{A}}$
- Wide Dynamic Range & 3D Noise Reduction  $\mathbf{Z}$
- Latest ONVIF compliant
- Alarm Input & Output / Audio Input & Output

## **SPECIFICATIONS**

Resolution	4 MP Imaging Sensor (2592 x 1520) Ultra High Definition
Video Compression	H.264 / H.265 / MJPEG
Resolution / fps	4MP @ 20fps / 3MP @ 30fps / 2MP @ 30fps
Minimum Illumination	0.1 lux Color / 0.01 lux B&W
Lens	Motorized 2.8-12mm Optical Zoom Lens with Autofocus
Day / Night	IR Cut Filter, Auto / Color / B&W
Alarm I/O	1 CH Alarm In / 1 CH Alarm Out
Audio I/O	1 CH Audio In / 1 CH Audio Out
BNC Video Service Output	YES
ONVIF Compliance	Latest ONVIF
Edge Recording	Micro SD Card Slot, Max 128GB (SD Card Not Included)
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Dimensions / Weight	111.5mm (H) x 110mm (D) Recessed Base / 1.10 lbs
Power	Class 3 PoE 802.3af / 12 VDC / Max 8 Watts





Wall Mount



AM7V2-KIT233IP Wall Mount & Back Box



3/4" Pendant Cap

innolech የ 1500 West Copans Road, Ste A-11 Pompano Beach, FL 33064

**(**) 954-792-2818

🖂 sales@innotechsecurity.com www.innotechsecurity.com