

EXCA322VIP2



**2 Megapixel - True Day/Night
IR Ball Dome IP Camera, 2.8-12mm
Varifocal Lens, 30 Meter IR Range,
IP66, PoE**

**2MP
HD
1080p**

**2.8-12mm
LENS
Varifocal**

**True
Day/Night**

**WDR
Wide
Dynamic
Range**

**3DNR
Noise
Reduction**

**ONVIF
Latest
Version**

**IP66
RATED**

2 Megapixel Imaging Sensor, Indoor/Outdoor IR Ball Dome IP Camera. True Day/Night Operation with ICR Cut Filter, Up to 30 meter IR Range (98 ft) & 2.8-12mm Varifocal Lens. Also features H.264 & MJPEG Multi Streaming, WDR, ROI, 3DNR, PoE, Latest ONVIF, IP66 Rated.

FEATURES

- ✓ 2 Megapixel Imaging Sensor - 1080p high definition resolution
- ✓ True Day/Night operation with ICR cut filter
- ✓ 2.8-12mm varifocal lens, 35.9 - 95.7° horizontal field of view
- ✓ Full 2MP @ 30fps main stream display & record
- ✓ Triple streaming for maximum network efficiency
- ✓ Up to 6Mbps bit rate
- ✓ IR range up to 30 meters (98 ft)
- ✓ Supports H.264 & MJPEG video compressions
- ✓ Digital Wide Dynamic Range, 3D Noise Reduction & ROI (Region of Interest)
- ✓ IP66 rated for outdoor use
- ✓ Latest ONVIF compliant

SPECIFICATIONS

Resolution	2 MP Imaging Sensor (1920 x 7080)
Video Compression	H.264 / MJPEG
Resolution / fps	2MP @ 30fps
Bit Rate (CBR / VBR)	Up to 6Mbps
Minimum Illumination	0 lux IR On: Color 0.002 lux / B&W 0.0002 lux
Lens	2.8-12mm Varifocal, 35.9 - 95.7° Horizontal FOV
Wide Dynamic Range	D-WDR
IR Range	Up to 30 meters (98 ft)
True Day/Night Operation	Yes, ICR Cut Filter
Digital Noise Reduction	Yes, 3DNR
ONVIF Compliance	Latest ONVIF
Environmental	IP66 Rated
Operating Temperature	-20°C to +50°C (-4°F to +122°F)
Power	Class 3 PoE 802.3af, Max 3 Watts (IR OFF), 5 Watts (IR On)
Dimensions / Weight	109mm W (4.3") x 130 H (5.1") / 687g (1.51 lbs.)
Ingress Protection	IP66

ACCESSORIES

EXNVR04V2-POE
4CH NVR w POE

EXNVR08V2-POE
8CH NVR w POE

EXNVR16V2-POE
16CH NVR w POE

EXNVR32-POE
32CH NVR w POE



AM108
Indoor
Wall Mount



AM101
Outdoor
Wall Mount



AM102
J-Box



AM103
Pendant
Mount